



Supplied Files

When assembling 'Print Ready' files please implement the relevant requirements from the previous links. As part of our Pre-Print Planning service Labelmakers has a team of dedicated Planning personal that are able to assist with any queries or specific areas of advice. Please note these specifications may change to suit to achieve the desired outcome for design & print.

Please refer to previous links for more specific details & supporting documents.

Please contact: Flexographic Technical Planning Scott Taylor (03) 9303-3320.

Lithographic Technical Planning Tracy Gallard (03) 9303-3370.

Print Ready files minimum requirements:

- All final signed proofs must be colour correct & signed with no alterations marked on proof. File must be true to proof.
- Ensure there is a correctly named colour swatch for each colour in file, remove unwanted colours in file.
- Cutter (Knife) or trim to be a spot colour with the name "Cutter".
- File names to have the version or revision number clearly marked on.
- Files supplied to be composite PDF's compatible (flattened/ no transparency).
- Files supplied for press are to be cropped of job strap and other extraneous information to minimum bleed.
- For sheet fed labels Allowance for Bleed 7.5mm Irregular Die cut Labels, 2.5mm for regular die cut (rectangle or Square labels) 1.5mm for Guillotine labels.
- Trapping Flexo 0.25mm Lithographic 0.15mm.
- Barcodes Flexo BWR 0.04 Lithographic BWR 0.02
- Any special ink/ laquers required must be on file, white Varnish spot, patterns etc. please have correct overprinting settings applied.